
NOTES:


- 1. Do not scale drawing. All dimensions given in inches (mm).
- 2. For strike preparation refer to:
 - 371 Strike Template No. 7102-0005
 - · 497 Strike Template No. 7102-0003
- 3. Backset: 2-3/4" (70mm) standard
- 4. For wood door preparation refer to: Template No. 80-8150-0034-010
- Door manufacturer must provide supports within the door to keep the door from collapsing when lock is installed. Back of latch case must also be supported.
- 6. Wire raceway required for hard power option. Raceway to connect Ø1" (25.4 mm) hole to hinge edge power source.


nexTouch™ Cylindrical Locks	
NTB610/612/613	Cylinder Override - Push Button
NTB620/622/623	Cylinder Override - Cap Touch
NTB630/632/633	No Cylindrical Override - Push Button
NTB640/642/643	No Cylindrical Override - Cap Touch



Dia. x Thru to

3/4"





RESPONSIBILITY

DOOR AND FRAME MANUFACTURERS ARE RESPONSIBLE FOR PROVIDING ADEQUATE CONSTRUCTION OR REINFORCEMENTS FOR PROPER INSTALLATION OF HARDWARE SHOWN. ALL ARCHITECTURAL BUILDERS HARDWARE MUST BE INSTALLED ON PROPERLY REINFORCED DOORS AND FRAMES, REGARDLESS OF TYPE, MATERIAL, OR METHOD OF CONSTRUCTION.

nexTouch™ Cylindrical Locks

H.M. Door Preparation 2-3/4" (70 mm) Backsets 800-810-9473 www.accentra-assaabloy.com

ACCENTRA ASSA ABLOY

Cross Bore

Ø 3/8" (9.5 mm)

Experience a safer and more open world

Copyright © 2022, 2024, ASSA ABLOY Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited.

SUPERSEDES 80-8150-0033-010 (09/22) DO NOT SCALE DRAWING

TEMPLATE NUMBER SHEET DATE

80-8150-0033-010 1 of 1 06/24